



## ARMSTRONG OASIS 90 RH

- Armstrong OASIS 90 RH is a 12mm white ceiling tile with a sandy surface resistant to abrasion and dust formation
- Good light reflectance (85%)





## **ARMSTRONG OASIS 90 RH**



Edge details	Board						
Additional edge details on request	Î						
Thickness (mm)	12						
Dimensions (mm)	600 x 600						
Additional sizes on request							
System	Exposed demountable - System C						
Weight	$3.3 \text{ kg} / \text{m}^2$						
Colour	White						
Sound absorption	EN ISO 354 $\alpha_{_{\rm w}}$ = <b>0.15(L)</b> as per EN ISO 11654 - <b>Class E</b>						
	Frequency f (Hz)	125	250	500	1000	2000	4000
	$\alpha_{\rm p}$ NRC = <b>0.15</b> as per ASTM C 423	0.30	0.25	0.15	0.10	0.10	0.20
Sound attenuation	EN ISO 10848-2 D <sub>n.f.w</sub> = <b>31 dB</b> as per EN ISO 717-1	CAC = <b>31 dB</b> as per ASTM E 413-10					
Fire reaction	Euroclass <b>B-s2,d0</b> as per EN 13501-1	RUS <b>KM1 (G1, V1, D1, T1)</b> as per 123-FZ					
Light reflectance	85%						
Thermal conductivity	λ = <b>0.060 W/mk</b> as per EN 12667						
Humidity resistance	90% RH						
Indoor air quality	DN 13964  A+  E1						
Cleanability							
Sustainability	ENISO 14021 40 - 44%						



